

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCEN
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
09/889,378	07/16/2001	Morio Yoshimoto	1163-0346P	2948	
2292	7590 02/26/2004		EXAMINER		
	EWART KOLASCH &	HOOSAIN, ALLAN			
PO BOX 747 FALLS CHURCH, VA 22040-0747			ART UNIT	PAPER NUMBER	
			2645		
			DATE MAILED: 02/26/2004	4 /	

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary		Application	on No.	Applicant(s)				
		09/889,37	'8	YOSHIMOTO ET AL.				
		Examiner		Art Unit				
		Allan Hoo		2645				
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply								
A SHOI THE M/ - Extensing after SI2 - If the perion of the	RTENED STATUTORY PERIOD FO AILING DATE OF THIS COMMUNIO ons of time may be available under the provisions of X (6) MONTHS from the mailing date of this commi- priod for reply specified above, the maximum sta- to reply within the set or extended period for reply by received by the Office later than three months af patent term adjustment. See 37 CFR 1.704(b).	CATION. of 37 CFR 1.136(a). In no eve unication.)) days, a reply within the statu tutory period will apply and wi will, by statute, cause the appl	ent, however, may a reply be tin utory minimum of thirty (30) day Il expire SIX (6) MONTHS from lication to become ABANDONE	nely filed s will be considered timely. the mailing date of this communi D (35 U.S.C. § 133).	ication.			
Status								
1)⊠ R	esponsive to communication(s) file	d on <i>Amendment B</i> ,	<i>12/16/03</i> .					
•	This action is FINAL. 2b)⊠ This action is non-final.							
3)□ S								
С	closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.							
Dispositio	n of Claims							
4)⊠ C	laim(s) <u>1-20</u> is/are pending in the a	pplication.						
48	4a) Of the above claim(s) is/are withdrawn from consideration.							
5)□ C	Claim(s) is/are allowed.							
6)⊠ C	Claim(s) <u>1-20</u> is/are rejected.							
7) 🗌 C	Claim(s) is/are objected to.							
8)□ C	claim(s) are subject to restric	tion and/or election re	equirement.					
Application	n Papers							
9)∐ Tł	ne specification is objected to by the	e Examiner.						
10)□ TI	10) ☐ The drawing(s) filed on is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.							
Α	Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).							
	Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).							
11)□ TI	ne oath or declaration is objected to	by the Examiner. No	te the attached Office	Action or form PTO-15	52.			
Priority un	der 35 U.S.C. § 119							
a)	cknowledgment is made of a claim to All b) Some * c) None of: Certified copies of the priority of the priority of the priority of the priority of the certified copies of the priority of the certified copies of application from the Internation of the attached detailed Office actions.	documents have bee documents have bee of the priority docume nal Bureau (PCT Rul	en received. en received in Applicati ents have been receive e 17.2(a)).	ion No ed in this National Stag	e			
Attachment(s	s) of References Cited (PTO-892)		4) Interview Summary	(PTO-413)				
	or References Cited (PTO-692) of Draftsperson's Patent Drawing Review (P	TO-948)	Paper No(s)/Mail D	ate				
	ntion Disclosure Statement(s) (PTO-1449 or No(s)/Mail Date	PTO/SB/08)	5) Notice of Informal F 6) Other:	Patent Application (PTO-152)				

Art Unit: 2645

DETAILED ACTION

Claim Rejections - 35 USC § 102

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

2. Claims 1-5, 7-13 and 17-20 are rejected under 35 U.S.C. 102(e) as being anticipated by Shaffer '490 (US 5,995,490).

As to Claim 1, with respect to Figures 1-2, **Shaffer '490** teaches a data communication device comprising:

a line state monitoring unit, 40, for detecting a line state relating to transmission quality in a communication line and producing line state information indicating the line state (Figure 1, label 36 and Col. 6, lines 1-10); and

a transmission control unit, 36, including a plurality of operation modes for transmitting data over the communication line, wherein the transmission unit is configured to select a specific operation mode from the operation modes based on an error tolerance level, which is determined according to the line state information produced by the line state monitoring unit, and perform

transmission control for continuously transmitting data regardless of the line state detected by the line state monitoring unit according to the specific operation mode (Col. 4, lines 24-37).

As to Claim 2, **Shaffer '490** teaches a data communication device according to claim 1, wherein the specific operation mode is changed to another operation mode by the transmission control unit in response to a change of the line state indicated by the line state information during the transmission of the data without suspending the transmission of the data, and the transmission control is performed for the transmission data according to the changed operation mode by the transmission control unit (Figure 2, label 58,66).

As to Claim 3, **Shaffer '490** teaches a data communication device according to claim 1, wherein: the transmission control unit has a plurality of data multiplexing methods corresponding to the operation modes,

a specific multiplexing method is selected from the multiplexing methods by the transmission control unit according to the line state information produced by the line state monitoring unit, and pieces of transmission data, which are planned to be sent out to the communication line, the specific multiplexing method being an optimal one of the plurality of multiplexing methods for transmitting data according to the determined error tolerance level, and pieces of transmission data, which are planned to be sent out to the communication line, are multiplexed with each other to a stream of multiplexed transmission data according to the specific multiplexing method (Col. 4, line 58 through Col. 5, line 3 and Col. 6, lines 30-40).

Page 4

Application/Control Number. Of

Art Unit: 2645

As to Claim 4, **Shaffer '490** teaches a data communication device according to claim 1, wherein the specific operation mode is changed to another operation mode corresponding to a high error tolerance level by the transmission control unit according to the line state information in cases where the line state information indicates a deteriorated line state, and the specific operation mode is changed to another operation mode corresponding to a low error tolerance level by the transmission control unit according to the line state information in cases where the line state information indicates an ameliorated line state (Col. 6, lines 30-45 and 56-65).

As to Claim 5, **Shaffer '490** teaches a data communication device according to claim 1, further comprising:

an operation mode change request receiving unit for receiving an operation mode change request from a second data communication device and sending the operation mode change request to the transmission control unit to make the transmission control unit perform the transmission control for the transmission data according to a particular operation mode indicated by the operation mode change request (Col. 6, lines 55-45 and 56-65).

As to Claim 7, **Shaffer '490** teaches a data communication device according to claim 1, further comprising:

a line interface for receiving and sending the transmission data to/from the communication line,

wherein the transmission control unit controls the line interface to increase a data transfer rate for data sending while decreasing a data transfer rate for data reception by a degree of the

increase of the data transfer rate for data sending in cases where the specific operation mode is changed to a particular operation mode corresponding to a high error tolerance level in the transmission control unit to perform the transmission control for the transmission data sent out to the communication line according to the particular operation mode (Col. 6, lines 55-65).

As to Claim 8, **Shaffer '490** teaches a data communication device according to claim 1, further comprising:

a line interface for receiving the transmission data from, and sending the transmission data to, the communication line,

wherein the transmission control unit controls the line interface to decrease a data transfer rate for data sending while increasing a data transfer rate for data reception by a degree of the decrease of the data transfer rate for data sending in cases where the specific operation mode is changed to a particular operation mode corresponding to a low error tolerance level in the transmission control unit to perform the transmission control for the transmission data sent out to the communication line according to the particular operation mode (Col. 6, lines 55-65).

As to Claim 9, with respect to Figures 1-2, **Shaffer '490** teaches a data communication device comprising:

a line state monitoring unit for detecting a line state relating to transmission quality in a communication line and producing line state information indicating the line state (Figure 1);

Art Unit: 2645

a transmission control unit including a plurality of operation modes for transmitting data over the communication line, wherein the transmission control unit is configured to select a specific operation mode from the operation modes based on an error tolerance level, which is determined according to the line state information produced by the line state monitoring unit, and perform a transmission control for continuously transmitting data regardless of the line state detected by line state monitoring unit, which is sent out to the communication line or is received through the communication line, according to the specific operation mode (Col. 4, line 58 through Col. 5, line 3); and

an operation mode change request outputting unit for requesting of a second data communication device, with which communication is performed through the communication line, that an operation mode selected in the second data communication device is changed to the specific operation mode selected by the transmission control unit (Col. 6, lines 30-45).

As to Claim 10, **Shaffer '490** teaches a data communication device according to claim 9, wherein the request of the operation mode change request outputting unit to the second data communication device is performed during the sending or reception of the transmission data without suspending the sending or reception of the transmission data (Col. 6, lines 30-45 and Col. 5, lines 30-42).

As to Claim 11, **Shaffer '490** teaches a data communication device according to claim 9, wherein:

Art Unit: 2645

the transmission control unit has a plurality of data multiplexing methods corresponding to the operation modes,

a specific multiplexing method is selected from the multiplexing methods by the transmission control unit according to the line state information produced by the line state monitoring unit, the selected multiplexing method being an optimal one of the plurality of data multiplexing methods for transmitting data according to the determined error tolerance level, and

the operation mode change request outputting unit requests the second data communication device, during the transmission of the data without suspending the transmission of the data to select the specific multiplexing method (Col. 4, lines 1-10 and Col. 5, lines 16-34).

As to Claim 12, **Shaffer '490** teaches a data communication device according to claim 9, wherein the operation mode change request outputting unit requests the second data communication device to change the specific operation mode to an operation mode corresponding to a high error tolerance level in cases where the line state information produced by the line state monitoring unit indicates a deteriorated line state, and the operation mode change request outputting unit requests the second data communication device to change the specific operation mode to an operation mode corresponding to a low error tolerance level in cases where the line state information produced by the line state monitoring unit indicates an ameliorated line state (Col. 6, lines 30-45).

As to Claim 13, **Shaffer '490** teaches a data communication device according to claim 9, further comprising:

an operation mode change request receiving unit for receiving an operation mode change request from the second data communication device, and sending the operation mode change request to the transmission control unit to make the transmission control unit perform the transmission control for the transmission data, which is received through the communication line or is sent out to the communication line, according to a particular operation mode indicated by the operation mode change request (Col. 6, lines 30-45).

As to Claim 17, **Shaffer '490** teaches a data communication device according to claim 9, further comprising:

a line interface for receiving and sending the transmission data from/to the communication line, wherein the transmission control unit controls the line interface to increase a data transfer rate for data sending while decreasing a data transfer rate for data reception by a degree of the increase of the data transfer rate for data sending, in cases where the specific operation mode is changed to a particular operation mode corresponding to a high error tolerance level in the transmission control unit to perform the transmission control for the transmission data sent out to the communication line according to the particular operation mode, and to increase a data transfer rate for data reception while decreasing a data transfer rate for data sending by a degree of the increase of the data transfer rate for data reception in cases where the specific operation mode is changed to a particular operation mode corresponding to a high error tolerance level in the transmission control unit to perform the transmission control for the transmission data received through the communication line according to the particular operation mode (Col. 6, lines 56-65 and Col. 7, lines 1-16).

As to Claim 18, **Shaffer '490** teaches a data communication device according to claim 9, further comprising:

a line interface for receiving and sending the transmission data from/to the communication line, wherein the transmission control unit controls the line interface to decrease a data transfer rate for data sending while increasing a data transfer rate for data reception by a degree of the decrease of the data transfer rate for data sending, in cases where the specific operation mode is changed to a particular operation mode corresponding to a low error tolerance level in the transmission control unit to perform the transmission control for the transmission data sent out to the communication line according to the particular operation mode, and to decrease a data transfer rate for data reception while increasing a data transfer rate for data sending by a degree of the decrease of the data transfer rate for data reception in cases where the specific operation mode is changed to a particular operation mode corresponding to a low error tolerance level in the transmission control unit to perform the transmission control for the transmission data received through the communication line according to the particular operation mode (Col. 6, lines 56-65 and Col. 7, lines 1-16).

As to Claim 19, **Shaffer '490** teaches a data communication device according to claim 13, further comprising:

a line interface for receiving transmission data from, and sending the transmission data to the communication line (Figure 1),

Art Unit: 2645

wherein the operation mode change request receiving unit further receives a data rate change request from the second data communication device, the operation mode change request receiving unit sends the data rate change request to the transmission control unit, the transmission control unit controls the line interface to increase a data transfer rate for data sending while decreasing a data transfer rate for data reception by a degree of the increase of the data transfer rate for data sending according to the data rate change request, in cases where the specific operation mode is changed to a particular operation mode corresponding to a high error tolerance level in the transmission control unit according to the operation mode change request to perform the transmission control for the transmission data sent out to the communication line according to the particular operation mode, and the transmission control unit controls the line interface to increase a data transfer rate for data reception while decreasing a data transfer rate for data sending by a degree of the increase of the data transfer rate for data reception according to the data rate change request in cases where the specific operation mode is changed to a particular operation mode corresponding to a high error tolerance level in the transmission control unit according to the operation mode change request to perform the transmission control for the transmission data received through the communication line according to the particular operation mode (Col. 6, lines 30-45, 56-65 and Col. 7, lines 1-16).

As to Claim 20, **Shaffer '490** teaches a data communication device according to claim 9, wherein the operation mode change request outputting unit requests the second data communication device to increase a data transfer rate for data sending while decreasing a data transfer rate for data reception by a degree of the increase of the data transfer rate for data

Application/Control Number: 09/889,378 Page 11

Art Unit: 2645

sending, in cases where the operation mode change request outputting unit requests the second data communication device to change the specific operation mode to a particular operation mode corresponding to a high error tolerance level in the transmission control unit according to the operation mode change request to perform the transmission control for the transmission data sent out to the communication line according to the particular operation mode, and the operation mode change request outputting unit requests the second data communication device to increase a data transfer rate for data reception while decreasing a data transfer rate for data sending by a degree of the increase of the data transfer rate for data reception in cases where the operation mode change request outputting unit requests the second data communication device to change the specific operation mode to a particular operation mode corresponding to a high error tolerance level in the transmission control unit according to the operation mode change request to perform the transmission control for the transmission data received through the communication line according to the particular operation mode (Col. 6, lines 30-45, 56-65 and Col. 7, lines 1-16).

Claim Rejections - 35 USC § 103

- 3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 4. This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was

Art Unit: 2645

commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

5. Claims 6, 14-16 are rejected under 35 U.S.C. 103(a) as being unpatentable over **Shaffer '490** in view of **Shaffer '668** (US 5,898,668).

As to Claims 6,14-16, **Shaffer** teaches a data communication device according to claim 1, further comprising:

a line state monitoring unit, 40, for detecting a line state relating to transmission quality in a communication line and producing line state information indicating the line state (Figure 1, label 36 and Col. 6, lines 1-10); and

a transmission control unit, 36, including a plurality of operation modes for transmitting data over the communication line, the transmission unit is configured to select a specific operation mode from the operation modes according to the line state information produced by the line state monitoring unit, and perform transmission control for continuously transmitting data regardless of the line state detected by the line state monitoring unit according to the specific operation mode (Col. 4, lines 24-37);

a line interface, connected with the communication line, for sending the transmission data to the communication line (Figure 1, label 30),

Art Unit: 2645

wherein the transmission control unit controls the line interface connected with the line interface, in cases where the specific operation mode corresponds to a high error tolerance level, and in cases where the specific operation mode is changed to a low error tolerance level;

Shaffer '490 does not teach the following limitation:

"add a new communication line" and "disconnect the new communication line"

However, it is obvious that **Shaffer '490** can be modified to accommodate the limitation. This is because **Shaffer '490** teaches connection to PSTN using one or more links (Figure 1 and Col. 3, lines 22-26). **Shaffer '668** teaches switch mode to different lines to enable QOS service levels (Figures 3-4 and Col. 8, lines 41-64). Having the cited art at the time the invention was made, it would have been obvious to one of ordinary skill in the art to add switch mode capability to **Shaffer '490** invention for interconnection to communication lines as taught by **Shaffer '668** invention in order to provide QOS requirements.

Response to Arguments

- 6. Applicant's arguments filed in the 12/16/03 Remarks have been fully considered but they are not persuasive because of the following:
 - (a) The arguments were already addressed in the 12/24/03 Advisory.
- (b) Examiner respectfully invites Applicants to contact Examiner to discuss possible amendments for overcoming the prior art of record.

Art Unit: 2645

Conclusion

7. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Stephenson et al. (US 4,730,313) teach monitoring ISDN channels for error thresholds and actions for overcoming the thresholds.

8. Any response to this action should be mailed to:

Commissioner of Patents and Trademarks Washington, D.C. 20231 or faxed to:

(703) 872-9314, (for formal communications intended for entry)

Or:

(703) 306-0377 (for customer service assistance)

Hand-delivered responses should be brought to Crystal Park II, 2121 Crystal Drive, Arlington. VA., Sixth Floor (Receptionist).

Any inquiry concerning this communication or earlier communications from the examiner should be directed to **Allan Hoosain** whose telephone number is (703) 305-4012. The examiner can normally be reached on Monday to Friday from 8 am to 4:30 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, **Fan Tsang**, can be reached on (703) 305-4895.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the Group receptionist whose telephone number is (703) 305-3900.

Allan Hoosain Primary Examiner 2/20/04